



22 Spring Valley Rd.
Paramus, NJ 07652
(201) 843-2400
sales@versa-valves.com

Bleed Control (3/4-14 NPT), SST

BC-6-316



Description

Stainless Steel Bleed Control Valve

The VERSA stainless steel Bleed Control Valves provide economical, effective flow control in pneumatic applications. They can be screwed into

the exhaust port of any VERSA directional control valve to offer "built-in" cylinder speed control.

Product Features

- Constructed of SAE 316L marine grade stainless steel conforming to NACE standard MR-01-75 suitable for direct exposure to sour environments

100% Leak Tested • 10-Year Warranty

Specifications

| | |
|----------------------------|----------------------------|
| Actuation | Adjustable stem w/lock nut |
| Port Size | Body Ported, 3/4" NPT |
| Valve Pressure Range (PSI) | 0-200 psi |
| Valve Pressure Range (BAR) | 0-13.8 bar |
| Primary Flow | 7.0 Cv |
| Media | Air - Inert Gas |
| Temperature Range (F) | -61°F to 300°F |
| Temperature Range (C) | -52°C to 149°C |
| Body & Internal Parts | 316L Stainless Steel |
| Weight | 0.450000 |

This spec sheet is intended for informational purposes only and while VERSA strives for accuracy, same does not constitute a warranty or guarantee, express or implied, regarding any products or services described herein. VERSA reserves the right to amend its product designs, details, specifications, and other information at any time without prior notice. VERSA also publishes information on its website at [VERSA-Valves.com](https://www.versa-valves.com) and information can be sought by contacting customer service at 201-843-2400 option 3, or emailing to sales@versa-valves.com.