



22 Spring Valley Rd.
Paramus, NJ 07652
(201) 843-2400
sales@versa-valves.com

Vent Screen 1/4" NPT, SST

MF-3-316



Description

Stainless Steel Vent Screen/Bug Screen

The VERSA stainless steel Vent Screens are threaded into the exhaust port of a directional control valve and offer effective protection against

dirt, dust, and insects entering the valve with minimal effect on flow.

Product Features

- Constructed of SAE 316 stainless steel conforming to NACE standard MR-01-75 suitable for direct exposure to sour environments

100% Leak Tested • 10-Year Warranty

Specifications

Actuation	NA
Port Size	Body Ported, 1/4" NPT
Valve Pressure Range (PSI)	0-300 psi
Primary Flow	0.080 Cv
Media	Air - Inert Gas
Temperature Range (F)	-40°F to 300°F
Temperature Range (C)	-40°C to 149°C
Body & Internal Parts	316 Stainless Steel
Weight	0.010000

This spec sheet is intended for informational purposes only and while VERSA strives for accuracy, same does not constitute a warranty or guarantee, express or implied, regarding any products or services described herein. VERSA reserves the right to amend its product designs, details, specifications, and other information at any time without prior notice. VERSA also publishes information on its website at [VERSA-Valves.com](https://www.versa-valves.com) and information can be sought by contacting customer service at 201-843-2400 option 3, or emailing to sales@versa-valves.com.