

Status indicator, SST, yellow - pressurized, green - depressurized

SI-2-316-403GY



Depressurized



Pressurized



Depressurized

Pressurized

Description

Stainless Steel Pressure Status Indicator

The VERSA stainless steel Status Indicator provides a visual notification of the pressure conditions in a system. The Status Indicator is housed within an engineered polymer shell that can be mounted on a panel. Viewing the panel provides the operator with an instantaneous evaluation of the pressure condition in the system or systems being monitored.

Product Features

- Constructed of SAE 316 stainless steel conforming to NACE standard MR-01-75 suitable for direct exposure to sour environments
- FKM o-ring seals perform reliably with exposure to hydrocarbons or highly corrosive fluids over a broad temperature range: equivalent to Viton®, Fluorel®

100% Leak Tested • 10-Year Warranty

Specifications

Actuation	Automatic shift with pressure loss
Port Size	Body Ported, 1/8" NPT
Valve Pressure Range (PSI)	8-200 psi
Valve Pressure Range (BAR)	0.55-13.8 bar
Media	Air - Inert Gas, Natural Gas
Temperature Range (F)	-9°F to 203°F
Temperature Range (C)	-23°C to 95°C
Body & Internal Parts	316 Stainless Steel
Weight	0.520000

This spec sheet is intended for informational purposes only and while VERSA strives for accuracy, same does not constitute a warranty or guarantee, express or implied, regarding any products or services described herein. VERSA reserves the right to amend its product designs, details, specifications, and other information at any time without prior notice. VERSA also publishes information on its website at [VERSA-Valves.com](https://www.versa-valves.com) and information can be sought by contacting customer service at 201-843-2400 option 3, or emailing to sales@versa-valves.com.